

# SOUTH PRAIRIE CREEK

# FLOODPLAIN AND OFF CHANNEL RESTORATION

SOUTH PUGET SOUND SALMON ENHANCEMENT GROUP





DRAWING LIST			
SHEET NUMBER	SHEET TITLE		
1	COVER SHEET		
2	GENERAL NOTES		
3	LEGEND		
4	EXISTING CONDITIONS		
5	TESC PLAN		
6	TESC DETAILS		
7	OVERALL SITE PLAN		
8	SITE 1		
9	SITE 2		
10	SITE 3		
11	SITE 4		
12	SITE 5		
13	SITE 6		
14	PROFILE 1		
15	PROFILE 2		
16	PROFILE 3		
17	CROSS SECTIONS 1		
18	CROSS SECTIONS 2		
19	ELJ 1 DETAILS		
20	ELJ 2 DETAILS		
21	DETAILS 1		
22	DETAILS 2		
23	DETAILS 3		
24	RE-VEGETATION PLANS - SITE 1		
25	RE-VEGETATION PLANS - SITE 2		
26	RE-VEGETATION PLANS - SITE 3		
27	RE-VEGETATION PLANS - SITE 4		
28	RE-VEGETATION PLANS - SITE 5		
29	RE-VEGETATION PLANS - SITE 6		
30	PLANT LISTS		
31	PLANTING DETAILS		

DDAMINIC LICT

### CONTACT INFORMATION

NATURAL SYSTEMS DESIGN, INC

1900 N NORTHLAKE WAY, SUITE 211 SEATTLE, WA 98103 (206) 834-0175

SOUTH PUGET SOUND SALMON ENHANCEMENT

6700 MARTIN WAY E, SUITE 112 OLYMPIA, WA 98516 (360) 412-0808













IAME OR INITIALS AND DATE	GEOGRAPHIC INFORMATION
ESIGNED M. HRACHOVEC	LATITUDE 47*08'15"N
HECKED T. ABBE	LONGITUDE 122'07'00"W
	TN/SC/RG T19N/S13/R5E
	DATE =
MEGNED	

SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION

**COVER SHEET** 

SHEET 1 OF 31

Jun-17-2014

- 2. NATURAL SYSTEMS DESIGN HEREAFTER REFERRED TO AS "ENGINEER" IS RESPONSIBLE FOR THE PREPARATION OF THESE ORIGINAL PLANS AND ASSOCIATED SPECIFICATIONS: AND WILL NOT BE RESPONSIBLE FOR, OR LIABLE FOR, UNAUTHORIZED CHANGE, OR USE, OF THESE PLANS WHICH INCLUDES ALTERATION, DELETION, OR EDITING OF THIS DOCUMENT WITHOUT EXPLICIT WRITTEN PERMISSION FROM THE ENGINEER. ANY OTHER UNAUTHORIZED USE OF THIS DOCUMENT IS PROHIBITED.
- 3. MINOR MODIFICATIONS ARE EXPECTED TO SUIT JOB SITE DIMENSIONS OR CONDITIONS. SUCH MODIFICATIONS SHALL BE INCLUDED AS PART OF THE WORK. THE OWNER, ENGINEER AND APPROPRIATE REGULATORY AGENCIES SHALL BE NOTIFIED OF ANY OWNER-AUTHORIZED CHANGE RESULTING IN MORE THAN A 10% DESIGN CHANGE OF PROPOSED FOOTPRINT OR THAT SIGNIFICANTLY AFFECTS THE INTENDED BENEFIT OR FUNCTION OF A PROJECT ELEMENT.
- 4. THE LOCATION OF ALL FEATURES SHOWN IS APPROXIMATE.
- 5. THE CONTRACTOR AGREES TO ASSUME SOLE AND COMPLETE RESPONSIBILITY FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THIS PROJECT, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY; AND FURTHER AGREES THAT THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS IN ACCORDANCE WITH THE PROVISIONS OUTLINED BY THE PROJECT CONTRACT AND SPECIFICATIONS.
- 6. ALL IMPROVEMENTS SHALL BE ACCOMPLISHED UNDER THE APPROVAL. INSPECTION. AND TO THE SATISFACTION OF THE OWNER. IMPROVEMENT CONSTRUCTION SHALL COMPLY WITH THESE PLANS AND THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (WSDOT) STANDARD PLANS FOR CONSTRUCTION OF ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION, CURRENT EDITION UNLESS NOTED OTHERWISE. ALL REFERENCES TO THE "STANDARD SPECIFICATIONS" SHALL MEAN THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (WSDOT) STANDARD SPECIFICATIONS FOR CONSTRUCTION OF LOCAL STREETS AND ROADS, CURRENT EDITION. CONSTRUCTION NOT SPECIFIED ON THESE PLANS SHALL CONFORM TO THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS. THE CONTRACTOR IS OBLIGATED TO BE FAMILIAR WITH APPLICABLE SECTIONS OF THE STANDARD SPECIFICATIONS NOT DISCUSSED IN THE GENERAL NOTES. THE CONTRACT SPECIAL PROVISIONS SHALL SUPERSEDE THOSE OF THE STANDARD SPECIFICATIONS WHERE DISCREPANCIES OCCUR.
- 7. IT IS THE RESPONSIBILITY OF THE CONTRACTOR AND SUBCONTRACTOR(S) TO EXAMINE THE PROJECT SITE PRIOR TO THE OPENING OF BID PROPOSALS. THE CONTRACTOR SHALL BECOME FAMILIAR WITH THE CONDITIONS UNDER WHICH THE WORK IS TO BE PERFORMED, SUCH AS THE NATURE AND LOCATION OF THE WORK; AND THE GENERAL AND LOCAL CONDITIONS, PARTICULARLY THOSE AFFECTING THE AVAILABILITY OF TRANSPORTATION, THE DISPOSAL, HANDLING, AND STORAGE OF MATERIALS, AVAILABILITY OF LABOR, WATER, ELECTRICITY, ROADS, THE UNCERTAINTIES OF WEATHER, THE CONDITIONS OF THE GROUND, SURFACE AND SUBSURFACE MATERIALS, GROUNDWATER, THE EQUIPMENT AND FACILITIES NEEDED FOR AND DURING THE PERFORMANCE OF THE WORK, AND THE COSTS THEREOF. ANY FAILURE BY THE CONTRACTOR AND SUBCONTRACTOR(S) TO ACQUAINT THEMSELVES WITH ALL THE AVAILABLE INFORMATION WILL NOT RELIEVE THE CONTRACTOR AND SUBCONTRACTOR(S) FROM RESPONSIBILITY FOR PROPERLY ESTIMATING THE DIFFICULTY AND COST OF SUCCESSFULLY PERFORMING THE WORK.
- 8. THE CONTRACTOR IS RESPONSIBLE FOR REVIEWING THE CONTRACT DOCUMENTS AND FOR ALL SUBMITTALS REQUIRED TO THE OWNER FOR REVIEW AND ACCEPTANCE.

#### PERMIT NOTES

- 1. EVERY REASONABLE EFFORT SHALL BE MADE TO CONDUCT THE ACTIVITIES SHOWN IN THESE PLANS, IN A MANNER THAT MINIMIZES THE ADVERSE IMPACT ON WATER QUALITY, FISH AND WILDLIFE, AND THE NATURAL ENVIRONMENT.
- 2. ALL WORK WILL BE IN COMPLIANCE WITH PERMIT CONDITIONS ISSUED BY PERTINENT REGULATORY AGENCIES. IT IS THE CONTRACTOR'S RESPONSIBILITY TO HAVE COPIES OF ALL PERMITS ON THE JOB SITE, UNDERSTAND AND COMPLY WITH ALL PERMIT CONDITIONS
- 3. ALL WORK THAT DISTURBS THE SUBSTRATE, BANK, OR SHORE OF A WATERS OF THE STATE THAT CONTAINS FISH LIFE SHALL BE CONDUCTED ONLY DURING THE WORK PERIOD FOR THAT WATERBODY AS ALLOWED BY RELEVANT HYDRAULIC WORK PERMITS. THOSE PORTIONS OF THE PROJECT WORK THAT OCCUR OUTSIDE OR ABOVE THE ORDINARY HIGH WATER MARK (ABOVE THE USACE JURISDICTIONAL LINE) ARE NOT SUBJECT TO THE WORK PERIODS DESCRIBED ABOVE UNLESS SPECIFIED IN THE RELEVANT PERMITS.
- 4. ALL ACTIVITIES THAT INVOLVE WORK ADJACENT TO, OR WITHIN THE WETTED CHANNEL SHALL, AT ALL TIMES, REMAIN CONSISTENT WITH ALL APPLICABLE WATER QUALITY STANDARDS; EFFLUENT LIMITATION; AND STANDARDS OF PERFORMANCE, PROHIBITIONS, PRETREATMENT STANDARDS, AND MANAGEMENT PRACTICES ESTABLISHED PURSUANT TO THE CLEAN WATER ACT OR PURSUANT TO APPLICABLE STATE AND LOCAL LAW.

- 5. IF AT ANY TIME, AS A RESULT OF PROJECT ACTIVITIES, FISH ARE OBSERVED IN DISTRESS, A FISH KILL OCCURS, OR WATER QUALITY PROBLEMS DEVELOP (INCLUDING EQUIPMENT LEAKS OR SPILLS), OPERATIONS SHALL CEASE AND THE OWNER SHALL BE NOTIFIED IMMEDIATELY.
- 6. IF, DURING CONSTRUCTION, ARCHAEOLOGICAL REMAINS ARE ENCOUNTERED, CONSTRUCTION IN THE VICINITY SHALL BE HALTED, AND THE STATE OFFICE OF HISTORIC PRESERVATION AND THE OWNER SHALL BE NOTIFIED IMMEDIATELY.

### SURVEY NOTES

- UNLESS NOTED OTHERWISE ON THE PLANS, THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING SURVEY MONUMENTS AND OTHER SURVEY MARKERS DURING CONSTRUCTION.
- 2. THE CONTRACTOR SHALL MAINTAIN A SET OF PLANS ON THE JOB SHOWING "AS-CONSTRUCTED" CHANGES MADE TO DATE. UPON COMPLETION OF THE PROJECT, THE CONTRACTOR SHALL SUPPLY TO OWNER A SET OF PLANS. MARKED UP TO THE SATISFACTION OF THE OWNER. REFLECTING THE AS-CONSTRUCTED MODIFICATIONS.
- 3. ELEVATIONS SHOWN ON THE PLANS FOR PIPE INVERTS, TOPS OF BANKS, THALWEG, GRADE CONTROLS, ETC., ARE BASED UPON THE TOPOGRAPHIC INFORMATION SHOWN ON THE PLANS. THE CONTRACTOR SHALL VERIFY ALL NECESSARY SURFACE ELEVATIONS IN THE FIELD AND NOTIFY THE OWNER OF ANY DISCREPANCIES, WHICH MIGHT AFFECT PROPER OPERATION OF THE NEW FACILITIES BEFORE BREAKING GROUND AND PRIOR TO FACILITY INSTALLATION. THE OWNER SHALL BE CONTACTED IN THE EVENT ELEVATIONS ARE INCORRECT SO THAT THE PROPER ADJUSTMENTS CAN BE MADE BY ENGINEER PRIOR TO THE INSTALLATION OF THE FACILITIES, AS SET FORTH IN THE SPECIAL PROVISIONS.
- LIDAR FOR THIS PROJECT WAS OBTAINED THROUGH PUGET SOUND LIDAR CONSORTIUM AND IS REPRESENTATIVE OF 2010 CONDITIONS. THE TOPOGRAPHIC SURVEY WAS PERFORMED BY LARSON AND ASSOCIATES AND ARE REPRESENTATIVE OF DECEMBER 2013 CONDITIONS. THE VERTICAL DATUM IS NAVD 88 (FT). THE HORIZONTAL DATUM IS WASHINGTON STATE PLANE SOUTH (FT).

### EROSION, SEDIMENT CONTROL AND WATER MANAGEMENT NOTES

- THE CONTRACTOR SHALL BE RESPONSIBLE FOR IMPLEMENTING ALL TEMPORARY EROSION CONTROL MEASURES. THE EROSION CONTROL MEASURES SHALL BE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REQUIREMENTS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE MAINTENANCE AND PERFORMANCE OF THE TEMPORARY EROSION CONTROL MEASURES THROUGHOUT THE DURATION OF THE PROJECT.
- 2. A SEDIMENT AND EROSION CONTROL PLAN WILL BE DEVELOPED BY THE CONTRACTOR AND SUBMITTED FOR APPROVAL BY OWNER AND/OR THE ENGINEER BEFORE ANY CONSTRUCTION MAY BEGIN. THE SEDIMENT AND EROSION CONTROL PLAN WILL IDENTIFY BEST MANAGEMENT PRACTICES TO ENSURE THAT THE TRANSPORT OF SEDIMENT TO SURFACE WATERS, DRAINAGE SYSTEMS, AND ADJACENT PROPERTIES IS MINIMIZED.
- 3. ACTIVITIES SHALL BE DESIGNED AND CONSTRUCTED TO AVOID AND MINIMIZE ADVERSE IMPACTS TO WATERS OF THE UNITED STATES TO THE MAXIMUM EXTENT PRACTICAL THROUGH THE USE OF PRACTICAL ALTERNATIVES. ALTERNATIVES THAT SHALL BE CONSIDERED INCLUDE THOSE THAT MINIMIZE THE NUMBER AND EXTENT OF IN—WATER WORK AND EQUIPMENT CROSSINGS OF WETTED CHANNELS.
- 4. AT NO TIME SHALL SEDIMENT-LADEN WATER BE DISCHARGED OR PUMPED DIRECTLY INTO THE SUBJECT RIVER, STREAM, OR WETLAND. WATER SHALL BE DISCHARGED IN ACCORDANCE WITH REQUIREMENTS SET FORTH IN THE PROJECT PERMITS AND / OR SPECIFICATIONS.
- 5. IF HIGH WATER LEVEL CONDITIONS THAT CAUSE SILTATION OR EROSION ARE ENCOUNTERED DURING CONSTRUCTION, WORK SHALL STOP UNTIL THE WATER LEVEL SUBSIDES.
- PERMIT CONDITIONS CONTAIN SPECIFIC REQUIREMENTS FOR THE CONTROL OF EROSION AND TURBIDITY FROM PROJECT OPERATIONS. TURBIDITY WILL BE MONITORED ON A FREQUENT BASIS BY THE PROJECT MANAGEMENT AND INSPECTION STAFF ON-SITE. TURBIDITY AMOUNTS IN EXCESS OF THE PERMITTED CONCENTRATIONS AND/OR DURATIONS WILL CAUSE WORK TO BE STOPPED UNTIL IMPROVED PRACTICES ARE IN EFFECT AND THE PROBLEMS CONTROLLED THE CONTRACTOR IS COMPLETELY RESPONSIBLE FOR ANY PROJECT DELAYS THAT OCCUR BY NATURE OF THIS FAILURE TO ADEQUATELY CONTAIN SEDIMENT ON-SITE.
- 7. CONTRACTOR SHALL LIMIT MACHINERY MOVEMENT TO CONSTRUCTION AREAS DEFINED ON SITE PLAN OR IDENTIFIED AS ACCEPTABLE BY THE ENGINEER OR OWNER.
- 8. ALL EXTERNAL GREASE AND OIL SHALL BE PRESSURE-WASHED OFF THE EQUIPMENT PRIOR TO TRANSPORT TO THE SITE.
- 9. THE CONTRACTOR IS RESPONSIBLE TO ENSURE THAT NO PETROLEUM PRODUCTS, HYDRAULIC FLUID, SEDIMENTS, SEDIMENT-LADEN WATER, CHEMICALS, OR ANY OTHER TOXIC OR DELETERIOUS MATERIALS ARE ALLOWED TO ENTER OR LEACH INTO THE SUBJECT RIVER

DATE

STREAM, OR WETLAND.

- 10. THE CONTRACTOR SHALL HAVE AN EMERGENCY SPILL KIT ONSITE AT ALL TIMES.
- 11. NO TREES OR WETLAND VEGETATION SHALL BE REMOVED UNLESS THEY ARE SHOWN AND NOTED TO BE REMOVED ON THE PLANS OR AS DIRECTLY SPECIFIED ON—SITE BY THE PROJECT MANAGEMENT STAFF. ALL TREES CONFLICTING WITH GRADING SHALL BE REMOVED. NO GRADING SHALL TAKE PLACE WITHIN THE DRIP LINE OF TREES NOT TO BE REMOVED UNLESS OTHERWISE APPROVED.
- 12. FOLLOWING CONSTRUCTION, SITE RESTORATION WILL INCLUDE ESTABLISHING LONG-TERM EROSION PROTECTION MEASURES. THESE MEASURES WILL INCLUDE PLANTINGS, EROSION CONTROL FABRIC, SEED, AND MULCH, EQUIPMENT AND EXCESS SUPPLIES WILL BE REMOVED AND THE WORK AREA WILL BE CLEANED. MAINTENANCE ACTIVITIES FOR THE NEWLY CONSTRUCTED RESTORATION PROJECTS ARE ANTICIPATED TO OCCUR PERIODICALLY.

### CONSTRUCTION NOTES

- 1. CONTRACT DOCUMENTS REFER TO THESE PLANS.
- 2. CONTRACTOR SHALL FURNISH ALL MATERIALS, EQUIPMENT, AND LABOR NECESSARY TO COMPLETE ALL WORK AS INDICATED IN THE CONTRACT DOCUMENTS.
- 3. CONSTRUCTION HOURS SHALL BE WEEKDAYS BETWEEN 7:00 A.M. AND 6:30 P.M. UNLESS PRIOR APPROVAL IS RECEIVED FROM THE OWNER.
- 4. ANY DISCREPANCIES ARE TO BE BROUGHT TO THE ATTENTION OF THE OWNER PRIOR TO PROCEEDING WITH THE WORK.
- 5. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY INDICATED OTHERWISE BY THE OWNER OR WHERE LOCAL CODES OR REGULATIONS TAKE PRECEDENCE.
- 6. ALL WORK PERFORMED AND MATERIALS INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES.
- 7. THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK USING THE BEST SKILLS AND ATTENTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES AND FOR COORDINATING ALL PORTIONS OF THE WORK UNDER THIS CONTRACT.
- THE CONTRACTOR SHALL MAKE ALL NECESSARY PROVISIONS TO PROTECT EXISTING IMPROVEMENTS, ROADWAY, DRAINAGE WAYS, PRIVATE BRIDGE, CULVERTS, AND VEGETATION UNTIL SUCH ITEMS ARE TO BE DISTURBED OR REMOVED AS INDICATED ON THE CONTRACT
- 9. THE CONTRACTOR SHALL KEEP THE JOB SITE CLEAN AND HAZARD FREE. CONTRACTOR SHALL DISPOSE OF ALL DIRT, DEBRIS, AND RUBBISH FOR THE DURATION OF THE WORK. UPON COMPLETION OF WORK, CONTRACTOR SHALL REMOVE ALL MATERIAL AND EQUIPMENT NOT SPECIFIED AS REMAINING ON THE PROPERTY
- 10. NOTES AND DETAILS ON THE PLANS SHALL TAKE PRECEDENCE OVER GENERAL NOTES HEREIN.
- 11. DIMENSIONS CALLOUTS SHALL TAKE PRECEDENCE OVER SCALES SHOWN ON THE PLANS.
- 12. THE PLANS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE METHOD OF ALL CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY TO PROTECT THE STRUCTURES, WORKS, AND THE PUBLIC DURING CONSTRUCTION.
- 13. MATERIAL SHALL NOT BE STORED OUTSIDE OF IDENTIFIED STAGING AREAS. THE CONTRACTOR SHALL USE ONLY DESIGNATED SPECIFIC SITES FOR STORAGE OF EQUIPMENT AND MATERIALS AS SHOWN ON THESE PLANS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SECURITY OF ALL EQUIPMENT AND MATERIALS.

Timothy B. Abbe
















GEOGRAPHIC INFORMATION TITUDE 47'08'15"N ONGITUDE 122°07'00"W TN/SC/RG T19N/S13/R5E

SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION

**COVER SHEET** 

SHEET 2 OF 31







EXISTING DECIDUOUS TREE


CONTROL POINT LOCATION













SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION


**LEGEND** 

3

SHEET **3** OF **31** 









### NOTES FOR "SUPER SACK" COFFER DAM DETAIL

- WRAP "SUPER SACKS" WITH IMPERVIOUS PLASTIC LINER TO PREVENT SEEPAGE.
- BACKFILL THE DOWNSTREAM SIDE COFFER DAM WITH NATIVE, ADJACENT ALLUVIUM.
- 3. USE "SUPER SACKS" AS BUTTRESSES AS REQUIRED.








#### NOTES FOR TEMPORARY CLEARED ACCESS


- CLEARED ACCESS TO BE ROUTED TO MINIMIZE VEGETATION DISTURBANCE AND FOREST CLEARING.
- 2. CONTRACTOR SHALL MARK CLEARING LIMITS WITH FLAGGING. CLEARING LIMITS TO BE APPROVED BY ENGINEER PRIOR TO ANY CLEARING ACTIVITIES.
- 3. ANY TREES GREATER THAN 18" Ø SHALL BE REMOVED W/ ROOTWADS INTACT AND STOCKPILED FOR USE IN LOGJAM CONSTRUCTION.
- TREES AND SHRUBS WITH 6"-18" Ø SHALL BE STOCKPILED FOR USE AS RACKING MATERIAL IN LOGJAM CONSTRUCTION.
- 5. REMAINDER OF VEGETATION AND ORGANIC SOIL SHALL BE GRUBBED, STOCKPILED AND BROADCASTED ON ROAD ALIGNMENT FOLLOWING TERMINATION OF WORK.
- 6. ACCESS SHALL BE MAINTAINED BY MINOR GRADING AND IMPORTATION OF WOOD CHIPS, GRAVEL AND/OR QUARRY SPALLS.
- 7. CLEARED ACCESS SHALL BE SCARIFIED AND DECONSTRUCTED TO PREVENT FUTURE ACCESS AT THE TERMINATION OF WORK.
- 8. REVEGETATION ROAD ALIGNMENT FOLLOWING CONSTRUCTION WILL BE PERFORMED BY
- 9. ALL GRAVEL OR QUARRY SPALLS PLACED SHALL BE UNDERLAIN WITH A GEOTEXTILE AND REMOVED AT TERMINATION OF WORK IF UTILIZED.

# TEMPORARY CLEARED ACCESS ROAD










- 1. CONTRACTOR TO DESIGN TEMPORARY BRIDGE.
- 2. BRIDGE SHALL BE LOCATED SUCH THAT ONLY ONE SPAN IS USED TO ELIMINATE IMPACTS TO SUBSTRATE OF CHANNEL.
- 3. END OF BRIDGE SHALL BEAR ON HIGH BANKS WITH SUFFICIENT BEARING CAPACITY TO PREVENT SLOUGHING OR COLLAPSE OF CHANNEL BANKS.
- 4. CONCRETE ECOLOGY BLOCKS OR WOOD ABUTMENTS MAY BE USED TO SUPPORT ENDS OF TEMPORARY BRIDGE AS NEEDED.
- 5. BRIDGES MAY BE CONSTRUCTED FROM LOGS, RAIL CAR BEDS OR APPROVED EQUAL AND DECKED WITH STEEL SHEET, WOOD LAGGING OR APPROVED EQUAL.

TEMPORARY LOG STRINGER BRIDGE



#### NOTES FOR TEMPORARY BAR ACCESS ROAD

- 1. BAR ACCESS ROADS TO BE ROUTED TO MINIMIZE VEGETATION DISTURBANCE.
- 2. CONTRACTOR SHALL STAKE EDGES OF PROPOSED BAR ACCESS ROAD FOR APPROVAL BY
- 3. EQUIPMENT SHALL OPERATE ONLY WITHIN STAKED BAR ACCESS ROAD ALIGNMENT OR OTHER DEFINED PROJECT AREAS.
- 4. BAR ACCESS ROAD SHALL BE SCARIFIED AT TERMINATION OF WORK.

TEMPORARY BAR ACCESS ROAD














SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION


TESC DETAILS


6


DESIGN


Jun-17-2014


SHEET 6 OF 31






























# PROFILE SCALE: H: 1" = 40' V: 1" = 10' 16



### FLOOD CHANNEL WEST PROFILE







## FLOOD CHANNEL SOUTH PROFILE















NAME OR INITIALS AND DATE	DATE GEOGRAPHIC INFORMATION		
DESIGNED M. HRACHOVEC	LATITUDE	47'08'15"N	
CHECKED T. ABBE	LONGITUDE	122*07'00"W	
DRAWN G. MATSUMOTO	TN/SC/RG	T19N/S13/R5E	
CHECKED M. HRACHOVEC	DATE		
***************************************			

SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION


PROFILE 3

SHEET 16 OF 31






1 EXCAVATED SCOUR HOLE



# BURIED LOG POST, TYP. (6) BACKFILL EXCAVATION 315 6 KEY MEMBER ELEVATION VARIES 515 8 RACKING MATERIAL CHANNEL BED 16 FLOW BOTTOM ELEVATION

# ELJ STRUCTURE SIDE PROFILE



Pierce

Vatural Systems Desig

### TYPE 1 STRUCTURE SCHEDULE

STRUCTURE LABEL*			
STRUCTURE WIDTH, (FT)	60		
STRUCTURE LENGTH, (FT)	75		
MINIMUM LOG DIAMETER, (IN)			
TIMBER POST DIAMETER, (IN)			
AVERAGE SEPTEMBER WATER SURFACE ELEVATION (FT-NAVD 88)			
**TBD - TO BE DETERMINED AND VERIFIED AT FINAL	DESIGN PH	HASE	

TYPE 1 ELJ — LOG SCHEDULE				
LOG ID	DIA* (IN)	LENGTH** (FT)	ROOTWAD (Y/N)	QUANTITY PER STRUCTURE
1	14	25	N	9
2	14	40	Y	5
3	14	40	OPTIONAL	3
* MINIMUM DIAMETER AT BREAST HEIGHT (2" MAXIMUM TAPER)				
** TOTAL LENGTH INCLUDING ROOTWAD				

# BACKFILL EXCAVATION 315 WITH NATIVE ALLUVIUM\* BURIED LOG POST 6 KEY MEMBER LOG 6 RACKING MATERIAL 8 PLOS. EXCAVATED SCOUR HOLE \* ONLY HALF OF BACKFILL SHOWN FOR CLARITY

### TYPE 1 ELJ STRUCTURE NOTES

- (1) EXCAVATE IN FRONT OF LOGJAM FOR PLACEMENT OF RACKING MATERIAL. EXCAVATION AREA SHALL NOT BE BACKFILLED WITH ALLUVIUM, BUT LEFT AS A SCOUR HOLE.
- 2. EXCAVATION SPOILS SHALL BE STAGED ACCORDING TO THE SWPPP. SPOILS SHALL ALSO BE STOCKPILED TO ALLOW LOG LAYER PLACEMENT AND CONSTRUCTION ACCESS.
- 3 BACKFILL EXTENTS MAY VARY AND TO BE CONSTRUCTED WITH NATIVE ALLUVIUM FROM EXCAVATION SPOILS.
- 4. BACKFILL EACH STRUCTURE LAYER WITH NATIVE ALLUVIUM FLUSH WITH THE CURRENT LAYER PRIOR TO PLACEMENT OF THE SUBSEQUENT LAYER.
- 5 FINAL ELJ HEIGHT TO BE ACHIEVED AS SPECIFIED REGARDLESS OF ACTUAL LOG DIAMETERS USED OR STACKING ARRANGEMENT.
- (6) ALL LARGE WOOD DIMENSIONS DO NOT INCLUDE BARK THICKNESS.
- 7. COVER TOP OF BACKFILL AREA AND BASE OF STRUCTURES 6-12 INCHES WITH LOOSE WOOD DEBRIS AND CHIPS.
- 8 RACKING MATERIAL SHALL CONSIST OF APPROXIMATELY X CU. YDS PER STRUCTURE WITH 6"-12" DIA DBH AND A MINIMUM OF X-FEET LENGTH. RACKING PLACEMENT SHALL OCCUR WITH EACH LAYER PLACEMENT TO ENSURE RACKING MATERIAL EXTENDS THROUGH STRUCTURE AND PINNED IN PLACE BY SUBSEQUENT LAYERS.
- 9. THE CONTRACTOR SHALL FIELD VERIFY WITH THE OWNER REPRESENTATIVE OR ENGINEER ALL STRUCTURE LOCATIONS, PILE LOCATIONS, LENGTHS, WIDTHS AND ELEVATIONS PRIOR TO EXCAVATION, ASSEMBLY AND INSTALLATION OF EACH
- 10. LOCATIONS FOR ALL STRUCTURE PLACEMENTS WILL BE STAKED IN FIELD BY THE ENGINEER OR OWNER REPRESENTATIVE PRIOR TO START OF CONSTRUCTION.
- 11. EXCAVATION LIMITS SHALL BE FIELD VERIFIED BY THE OWNER REPRESENTATIVE OR ENGINEER PRIOR TO EXCAVATION COMMENCING AND PLACEMENT OF ANY LARGE WOOD.
- 12. LOG TYPE IDENTIFICATION SHALL BE PAINTED ON ALL LOGS BY THE CONTRACTOR IN A PLACE VISIBLE FOR FIELD VERIFICATION PRIOR TO PLACEMENT WITH LEAD-FREE, BLAZE-ORANGE SURVEY MARKING PAINT.
- 13. THE WOOD LAYER PLACEMENT IN EACH LOGJAM LAYER SHALL BE FIELD VERIFIED BY ON-SITE OWNER REPRESENTATIVE PRIOR TO BACKFILLING.
- [5] BACKFILL NOT TO EXCEED TOP ELEVATION. EXCESS BACKFILL TO BE PLACED
- (16) CHANNEL BED ELEVATION IS REPRESENTATIVE OF A LOCAL AVERAGE CHANNEL BED AT RIFFLES. CHANNEL BED ELEVATION SHOULD NOT BE TAKEN IN POOLS.




**ELJ STRUCTURE PERSPECTIVE** 

	NAME OR INITIALS AND DATE	GEOGRAPHIC INFORMATION	
gn	DESIGNED	LATITUDE	
3	CHECKED	LONGITUDE	
7	DRAWN	TN/SC/RG	
	CHECKED	DATE	


**ELJ 1 DETAILS** 

19


SHEET 19 OF 31



SCALE: 1" = 10"



PROFILE SCALE: 1" = 10"







NOT TO SCALE

### STREAMBED COBBLE GRADATIONS


ONADATIONS		
D16	3"	
D50	6"	
D84	10"	
D100	14"	




PLACE 3 ROOTWADS IN TRIANGULAR SHAPE, CONNECT WITH CROSS CABLE LASHING.



LAYER 2 PLACE RACKING MATERIAL IN CHANNEL. LIFT AND PLACE TYPE 3 UNIT IN CHANNEL ON TOP OF RACKING MATERIAL USING A 3-POINT HARNESS WHICH ATTACHES TO THE CENTER OF EACH LOG. ADD ROCK COLLARS AT EACH INTERSECTION.



LAYER 3 ADD 2 POSTS. POSTS ARE TO BE PLACED AGAINST THE ROOTWAD MOST FACING TOWARD THE FLOW. CABLE LASH ROOTWAD TO POSTS.



LAYER 4 FILL VOIDS WITH STREAMBED COBBLE (CHANNEL SPANNING STRUCTURE #1 ONLY).

# TYPE 2 UNIT LAYERING PLANS

### TYPE 2 STRUCTURE NOTES:

- 1. FOR PLACEMENT AND CONFIGURATION OF TYPE 3 ELJ UNITS SEE SHEET 15. THE TYPE 3 ELJ UNIT TURNED OVER IS THE SAME ROOTWAD CONFIGURATION AS THE TYPE 3 ELJ UNIT BUT TURNED UPSIDE DOWN. 2. THE TOPS OF THE PILES ARE TO BE APPROX. 1' ABOVE ADJACENT LOG AT MOST UPSTREAM TYPE 3 UNITS AND 1'-2' ABOVE ADJACENT LOG AT DOWNSTREAM TYPE 3 UNITS.. PILES ARE TO BE DRIVEN USING VIBRATORY METHODS.

  - TYPE 3 UNIT TO BE ASSEMBLED IN THE DRY AND PLACED IN THE CHANNEL.

    NO IN—CHANNEL EXCAVATION SHALL OCCUR DURING THE CONSTRUCTION OF THE TYPE 3 ELJ. TYPE 3 UNITS SHALL BE PLACED DIRECTLY ON THE CHANNEL BED AND PRESSED DOWN INTO THE CHANNEL TO MINIMIZE GAPS BETWEEN THE CHANNEL AND LOG. AT NO TIME SHALL EQUIPMENT BE IN CONTACT WITH THE CHANNEL BED.

    EACH TYPE 3 UNIT SHALL BE BALLASTED WITH THREE ROCK COLLARS ON EACH CORNER.

  - CLEAN STREAMBED COBBLE SHALL BE PLACED IN INTERSTITIAL SPACES IN EACH TYPE 3 UNIT. STREAMBED COBBLE TO BE UP TO 3-FT DEEP AND 5-FT UPSTREAM OF THE MOST UPSTREAM TYPE 3 UNIT TO CREATE A SMOOTH TRANSITION FROM THE EXISTING CHANNEL TO THE TOP OF LOG. STREAMBED COBBLE TO BE CLEAN AND WASHED TO MINIMIZE TURBIDITY DURING PLACEMENT.

    THE CONTRACTOR SHALL FIELD VERIFY WITH THE OWNER REPRESENTATIVE OR ENGINEER ALL STRUCTURE LOCATIONS, PILE LOCATIONS, LENGTHS, WIDTHS AND ELEVATIONS PRIOR TO EXCAVATION, ASSEMBLY AND
- INSTALLATION OF EACH STRUCTURE.

  8. LOCATIONS FOR ALL STRUCTURE PLACEMENTS WILL BE STAKED IN FIELD BY THE ENGINEER OR OWNER REPRESENTATIVE PRIOR TO START OF CONSTRUCTION.

  9. THE WOOD LAYER PLACEMENT IN EACH LOGJAM LAYER SHALL BE FIELD VERIFIED BY ON—SITE OWNER REPRESENTATIVE PRIOR TO PLACEMENT.

  10. TYPE 2 ELJ UNITS SHALL BE USED FOR CHANNEL SPANNING STRUCTURES 1—3.













	NAME OR INITIALS AND DATE	GEOGRAPH	IC INFORMATION
istems Design	DESIGNED MH HRACHOVEC	LATITUDE	47'08'36"N
		LONGITUDE	122°07'00"W
	DRAWN GD MATSUMOTO	TN/SC/RG	T29N/S19/R5EW
		DATE	

SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION


# TYPE 2 ELJ UNIT - LOG SCHEDULE

LOG ID	DIA* (IN)	LENGTH** (FT)	(Y/N)	QUANTITY PER STRUCTURE
10	24	40	Y	3
12	16	20	N	2
* DIAMETER AT BR	EAST HEIGHT, NOT	INCLUDING BARK T	HICKNESS	
** TOTAL LENGTH INCLUDING ROOTWAD				

**ELJ 2 DETAILS** 

20

SHEET 20 OF 31



- 3 FILL TO BE 70/30 MIX OF STREAMBED BOULDERS AND 12" STREAMBED COBBLES.
- 4 MATCH EXISTING GRADE.
- 5 BOULDER CASCADE.

PLAN VIEW SCALE: 1"=20"



CHANNEL SPANNING STRUCTURE #4 1















IE OR INITIALS AND DATE	GEOGRAPHIC INFORMATION		
GNED M. HRACHOVEC	LATITUDE	47'08'15"N	
CKED T. ABBE	LONGITUDE	122'07'00"W	
		T19N/S13/R5E	
	DATE	_	
CKED M. HICACHOVEC	DAIL		

SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION


DETAILS 1

21

SHEET 21 OF 31

60% DESIGN

# TO BE DETERMINED











	NAME O	R	II
is Design	DESIGNED	М.	1
	CHECKED	т.	1
	DRAWN	G.	١
	CHECKED	м.	_

INITIALS AND DATE

SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION

DETAILS 2

22

SHEET 22 OF 31

60% DESIGN

Jun-17-2014

# TO BE DETERMINED
















AME OR INITIALS AND DATE	GEOGRAPH	IIC INFORMA
ESIGNED M. HRACHOVEC	LATITUDE	47'08'15"N
HECKED T. ABBE	LONGITUDE	122'07'00"W
RAWN G. MATSUMOTO	TN/SC/RG	T19N/S13/F
	DATE	


SOUTH PRAIRIE CREEK FLOODPLAIN AND OFF CHANNEL RESTORATION


DETAILS 3


23


SHEET 23 OF 31




















60% DESIGN

Jun-17-2014